

**Таблица характеристик погружных взрывозащищённых насосов  
Промхиммаш Серия 1000.**

типоразмер	подача (м <sup>3</sup> /ч)	Напор (м)	Обороты (об/мин)	Мощность (кВт)	КПД (%)	ДУ (мм)
10-15-1.5	10	15	3000	1.5	31	50
15-16-1.5	15	16			32.5	
25-7-1.5	25	7			35.5	
15-22-2.2	15	22		2.2	36	
25-10-2.2	25	10			36	
35-7-2.2	35	7			38	
10-32-3	10	32		3	31	
15-25-3	15	25			31.5	
25-15-3	25	15			37	
40-12-3	40	12			41.5	
52-7-3	52	7			41.5	80
15-32-4	15	32		4	34.6	50
20-30-4	20	30			41	
25-22-4	25	22			37.8	
50-15-4	50	15			43.3	80
75-8-4	75	8			44	100
12-50-5.5	12	50		5.5	33	50
20-40-5.5	20	40			34	
30-30-5.5	30	30			44	
40-20-5.5	40	20			44.5	
70-15-5.5	70	15	45.8		80	

100 - 10 - 5.5	100	10			52.5	100
25 - 50 - 7.5	25	50			46.7	50
30 - 36 - 7.5	30	36			44.5	
50 - 30 - 7.5	50	30			55	
75 - 20 - 7.5	75	20			55	
100 - 15 - 7.5	100	15			55.3	
145 - 10 - 7.5	145	10	3000	7.5	56.5	150
20 - 65 - 11	20	65			38.6	50
40 - 40 - 11	40	40			46	80
50 - 35 - 11	50	35			56	
80 - 20 - 11	80	20			56.5	100
150 - 15 - 11	150	15			55.8	150
200 - 10 - 11	200	10			57.5	
40 - 50 - 15	40	50			44	80
60 - 35 - 15	60	35			45.3	100
100 - 22 - 15	100	22			48.6	
170 - 18 - 15	170	18			56.5	150
200 - 15 - 15	200	15			57	
300 - 10 - 15	300	10			58	200
80 - 35 - 18.5	80	35			47	100
100 - 30 - 18.5	100	30			48	
150 - 25 - 18.5	150	25			57.5	150
250 - 15 - 18.5	250	15			59	200
40 - 80 - 22	40	80			44	80
60 - 50 - 22	60	50			45.8	
80 - 40 - 22	80	40			47	
150 - 30 - 22	150	30			59.3	

200-20-22	200	20		30	60	
300-15-22	300	15			61	200
80-60-30	80	60			48.5	80
120-50-30	120	50			57.8	150
200-30-30	200	30			59	
300-20-30	300	20			61	200
400-15-30	400	15	1500	30	63	200
100-70-37	100	70		37	58.5	100
150-45-37	150	45			62	150
350-25-37	350	25			69.5	200
500-15-37	500	15			72	250
150-50-45	150	50		45	57	150
400-25-45	400	25			66	200
500-20-45	500	20			67	250
600-15-45	600	15			69	
150-70-55	150	70		55	58	150
200-50-55	200	50			59	
400-30-55	400	30			66.6	200
500-25-55	500	25	68.3		250	
600-20-55	600	20	68.5			
200-70-75	200	70	75		58	150
300-50-75	300	50		60.5	200	
400-40-75	400	40		67		
600-28-75	600	25		68	250	
800-20-75	800	20		69	300	
220-70-90	220	70		90	58.5	150
300-60-90	300	60	62		200	

500-35-90	500	35			64		
900-20-90	900	20			70	300	
400-60-110	400	60			110	69.8	200
600-40-110	600	40				70	250
700-32-110	700	32				71.5	
1000-25-110	1000	25			73	300	
600-50-132	600	50	1500	132	70	200	
500-60-132	500	60			69		
800-35-132	800	35			69.8	250	
1000-30-132	1000	30			80	300	
700-50-160	700	50	160	71.3	250		
1000-35-160	1000	35		75	350		
1500-25-160	1500	25		76.5	400		
2000-20-160	2000	20		80			
800-50-185	800	50	185	72.3	250		
1000-40-185	1000	40		73.8	300		
1500-30-185	1500	30		74.9	400		
2500-18-185	2500	18		81.4	500		
1200-40-200	1200	40	200	76	350		
1500-32-200	1500	32		77.4	400		
2000-25-200	2000	25		80			
3000-16-200	3000	16		79.8	500		